

SIEMENS



[usa.siemens.com/lv-drives](http://usa.siemens.com/lv-drives)

# SINAMICS and SIMOTICS

Low-voltage drives and motors line card

Answers for industry.

# SINAMICS low-voltage — general purpose drives

Common applications such as pumps, fans, compressors and conveyors

General purpose AC drives — open	General purpose AC drives — enclosed
<b>SINAMICS V20</b> <ul style="list-style-type: none"> <li>The perfect drive solution for basic applications (pumps, fans, compressors, conveyors)</li> <li>380–480V 3-phase, 0.5–20 hp</li> <li>200–240V 1-phase, 0.16–4 hp</li> <li>V/f, V2/f, FCC, V/f multi-point</li> <li>Optional parameter loader</li> <li>Through-the-wall and side-by-side mounting</li> </ul> 	<b>SINAMICS G110D</b> <ul style="list-style-type: none"> <li>Distributed drive</li> <li>380–500V 3-phase, 1–10 hp</li> <li>IP65 watertight enclosure</li> <li>Disconnect and local remote switch</li> <li>V/Hz</li> </ul> 
<b>SINAMICS G120C</b> <ul style="list-style-type: none"> <li>For three-phase applications such as conveyor belts, material transport, pumps, fans and machine tools.</li> <li>380–480V 3-phase, 0.75–25 hp</li> <li>V/Hz and sensorless vector</li> <li>Safety Integrated</li> </ul> 	<b>SINAMICS G120D</b> <ul style="list-style-type: none"> <li>Distributed drive — regenerative power module</li> <li>380–500V 3-phase, 1–10 hp</li> <li>IP65 watertight enclosure</li> <li>V/Hz, vector</li> <li>Safety Integrated</li> </ul> 
<b>SINAMICS G120 Modular</b> <ul style="list-style-type: none"> <li>Modular design concept</li> <li>Regenerative power module</li> <li>380–480V 3-phase, 0.5–400 hp</li> <li>500–690V 3-phase, 15–75 hp (non UL)</li> <li>V/Hz, vector and sensorless vector</li> <li>Closed loop control available</li> <li>Safety Integrated basic (STO, SS1, SCC) and extended (STO, SS1, SBC, SLS, SSM, SDI)</li> </ul> 	<b>SINAMICS G120P</b> <ul style="list-style-type: none"> <li>Pump and fan drive</li> <li>Optimized power efficiency</li> <li>380–480V 3-phase, 0.5–125 hp</li> <li>V/Hz and sensorless vector</li> <li>IP55 / UL TYPE 12 (frame sizes A through C)</li> </ul> 
<b>SINAMICS G130</b> <ul style="list-style-type: none"> <li>High-power chassis drive</li> <li>380–480V 3-phase, 150–800 hp</li> <li>500–600V 3-phase, 150–800 hp</li> <li>660–690V 3-phase, 75–800 kW</li> <li>V/Hz, vector and sensorless vector</li> <li>Safety Integrated — basic and extended</li> </ul> 	<b>SINAMICS G120E</b> <ul style="list-style-type: none"> <li>NEMA 1 and 12 Enclosures</li> <li>380–480V 3-phase, 1–200 hp</li> <li>6- or 18-pulse, or efficient infeed</li> <li>UL listing — standard</li> <li>G120 modular power modules</li> <li>Standard input circuit breaker, control power transformer and IOP operator interface</li> <li>Safety Integrated — basic and extended</li> </ul> 
<b>MICROMASTER 420</b> <ul style="list-style-type: none"> <li>Family of single- and three-phase drives for industrial motor control</li> <li>200–240V 1-phase, 0.16–4 hp</li> <li>200–240V 3-phase, 0.16–7.5 hp</li> <li>380–480V 3-phase, 0.5–15 hp</li> </ul> 	<b>SINAMICS G150-C</b> <ul style="list-style-type: none"> <li>NEMA 1 and 12 Enclosures</li> <li>380–480V 3-phase, 150–800 hp</li> <li>500–600V 3-phase, 150–800 hp</li> <li>AOP30 operator interface standard</li> <li>CU320-2 with Profibus standard</li> <li>CE mark; optional UL listing</li> <li>IEC design available</li> <li>Safety Integrated — basic and extended</li> </ul> 
<b>MICROMASTER 430 / 440</b> <ul style="list-style-type: none"> <li>Family of single- and three-phase drives for industrial motor control</li> <li>200–240V 1-phase, 0.16–4 hp</li> <li>200–240V 3-phase, 7.5–75 hp</li> <li>380–480V 3-phase, 0.5–350 hp</li> <li>500–600V 3-phase, 2–120 hp</li> <li>V/Hz, vector (with and without encoder)</li> </ul> 	<b>SINAMICS G150-A</b> <ul style="list-style-type: none"> <li>NEMA 1 and 12 enclosures</li> <li>380–480V 3-phase, 150–800 hp</li> <li>500–600V 3-phase, 150–800 hp</li> <li>Input circuit breaker standard</li> <li>Input reactor standard</li> <li>AOP30 operator interface standard</li> <li>CU320-2 with Profibus standard</li> <li>Safety Integrated — basic and extended</li> <li>CE mark; optional UL listing</li> <li>IEC design available</li> </ul> 

# SINAMICS low-voltage — high performance drives

Demanding applications such as centrifuges, extruders, metal processing and forming, motion control and test stands

High-performance drives — open		High-performance drives — enclosed	
<b>SINAMICS S110 AC / AC</b> <ul style="list-style-type: none"> <li>Single-axis positioning drive</li> <li>200–240V 1-phase, 0.16–0.75 hp</li> <li>380–480V 3-phase, 0.5–100 hp</li> <li>Basic positioning tasks</li> <li>Servo control</li> <li>Safety Integrated — basic and extended</li> </ul>		<b>SINAMICS S150 AC / AC</b> <ul style="list-style-type: none"> <li>Single drives for test bays, cutters, centrifuges, conveyor belts and presses</li> <li>380–480V 3-phase, 150–1150 hp</li> <li>500–690V 3-phase, 75–1250 hp</li> <li>Active line module (standard)</li> <li>Four quadrant operation (standard)</li> <li>Safety Integrated — basic and extended</li> </ul>	
<b>SINAMICS S120 AC / AC</b> <ul style="list-style-type: none"> <li>Single-axis performance drive</li> <li>200–240V 1-phase, 0.16–0.75 hp</li> <li>380–480V 3-phase, 0.5–400 hp</li> <li>Motion control and positioning tasks</li> <li>Vector, servo, V/Hz control</li> <li>Safety Integrated — basic and extended</li> </ul>		<b>SINAMICS S120M decentralized servo</b> <ul style="list-style-type: none"> <li>Integrated servomotor and drive</li> <li>510–720V DC, 0.25–1.5 kW</li> <li>Motion control and positioning tasks</li> <li>Hybrid cable technology</li> <li>Safety Integrated — basic and extended</li> </ul>	
<b>SINAMICS S120 multi-axis</b> <ul style="list-style-type: none"> <li>Common DC bus drive system</li> <li>Air-cooled, external air-cooled, liquid cooled</li> <li>380–480V 3-phase, 1.0–1150 hp</li> <li>500–690V 3-phase, 75–1250 hp</li> <li>Basic, regenerative and active infeeds</li> <li>Motion control and positioning tasks</li> <li>Vector, servo, V/Hz control</li> <li>Safety Integrated — basic and extended</li> </ul>		<b>SINAMICS S120CM DC / AC</b> <ul style="list-style-type: none"> <li>Modular cabinet system for multi-motor drives with a common DC bus bar.</li> <li>Typical applications include paper machines, rolling mills, test stands and hoisting gear.</li> <li>380–480V 3-phase, 150–4000 hp</li> <li>500–690V 3-phase, 75–5000 hp</li> <li>Line-ups consist of line connection module, line modules and motor modules.</li> <li>Basic, regenerative and active infeeds</li> <li>CE mark; optional UL listing</li> <li>Safety Integrated — basic and extended</li> </ul>	
High-performance DC drive solutions			
<b>SINAMICS DCM</b> <ul style="list-style-type: none"> <li>Combines the strength of the SIMOREG 6RA70 with that of the SINAMICS drives</li> <li>Supply of both the armature and the field</li> <li>Two-quadrant, non-regen 400–950V AC (485–1140V DC) 60–3000A IEC</li> <li>Four-quadrant, regen 400–950V AC (485–1000V DC) 15–3000A (IEC)</li> </ul>		<b>SINAMICS DCM control module</b> <ul style="list-style-type: none"> <li>Used for retrofitting or upgrading</li> <li>Only the control unit is replaced</li> <li>Allows for a state-of-the-art DC drive with fully functional digitized units from the SINAMICS DC MASTER series</li> <li>24V DC electronic power supply</li> <li>Integrated field power unit</li> <li>Compact design and can be split depth-wise</li> <li>Coated modules</li> <li>Wide temperature range</li> </ul>	
<b>SINAMICS DCM Cabinet</b> <ul style="list-style-type: none"> <li>Ready-to-connect and ready-to-switch-on</li> <li>Fast and straightforward installation, parameterization and commissioning</li> <li>Compact — individual components and interfaces are easily accessed</li> <li>Wide range of options for maximum flexibility</li> <li>Integrated power supply for the external fan of the DC motor</li> <li>Menu-prompted commissioning using the advanced operator panel or PC-based tool</li> <li>IP21 through IP54 enclosure options</li> <li>400–950V 3-phase incoming options</li> <li>485–1140V DC two-quadrant, 60–2200A</li> <li>420–1000V DC four-quadrant, 15–2200A</li> </ul>		<b>SINAMICS DCM base drive (DCII-rated)</b> <ul style="list-style-type: none"> <li>Consists of the converter mounted on a base panel with the addition of line fuses, AC line contactor (DC contactor 1200A unit only), DC output fuses (regen units), field fuses and control power transformer</li> <li>Two-quadrant, non-regen 240V AC (240V DC), 3–250 hp 480V AC (500V DC), 3–500 hp</li> <li>Four-quadrant, regen 240V AC (240V DC), 3–250 hp 480V AC (500V DC), 3–500 hp</li> <li>Custom designed above 500 hp are available upon request</li> </ul>	


# SIMOTICS motors for motion control applications

Quality, performance and efficiency

## High-performance inverter duty motors

### SIMOTICS-S — 1FK servomotors

- Compact synchronous motors for standard motion control applications
- Torque: 0.18–48 Nm
- Power: 0.05–8.17 kW
- Rated speeds: 2000, 3000, 4500, 6000 rpm
- Dynamic performance versions: high inertia, compact and high-dynamic
- Overload capability up to 400%
- Either incremental or absolute encoder with DRIVE-CLiQ
- Natural cooling




### SIMOTICS-M — 1PH8 main spindle motors

- Flexible, dynamic power for precision rotary axes applications
- Torque: 13–12,475 Nm
- Power: 2.8–1340 kW
- Rated Speeds: 600, 100, 1350, 2000, 3400, 3600 rpm
- Maximum speeds up to 20,000 rpm
- Induction and synchronous versions
- Water cooling, forced-cooling, open-circuit cooling
- Either incremental or absolute encoder with DRIVE-CLiQ; sensorless also available



### SIMOTICS-S — 1FT servomotors

- Compact synchronous motors for high-performance motion control applications
- Torque: 2–25 Nm
- Power: 0.88–34.2 kW
- Rated speeds: 1500, 2000, 3000, 4500 and 6000 rpm
- Dynamic performance versions: high inertia, compact and high-dynamic
- Overload capability up to 400%
- Either incremental or absolute encoder with DRIVE-CLiQ
- Natural cooling, water-cooling, forced-cooling



### SIMOTICS-T — 1FW torque motors

- Complete series of torque motors for up to 7000 Nm
- Torque: 100–20,000 Nm
- Power: 3.1–380 kW
- Rated Speeds: 170, 300, 360, 480, 600, 730, 890, 950 and 1450 rpm
- Versions with solid / hollow / slip-on shaft
- Compact, rugged and low-maintenance
- Space-saving alternative to motor / gearbox combinations, e.g. to drive rolls and rotary indexing tables
- Water cooling, forced cooling, open-circuit cooling
- Either incremental or absolute encoder with DRIVE-CLiQ



Siemens Industry, Inc.  
5300 Triangle Parkway, Suite 100  
Norcross, GA 30092

1-800-879-8079  
mcs.motioncontrol.industry@siemens.com

Order No. MOBR-LVDLC-0214

Printed in USA  
© 2014 Siemens Industry, Inc.

[usa.siemens.com/motioncontrol](http://usa.siemens.com/motioncontrol)

This brochure contains only general descriptions or performance features, which do not always apply in the manner described in concrete application situations or may change as the products undergo further development. Performance features are valid only if they are formally agreed upon when the contract is closed.

Siemens is a registered trademark of Siemens AG. Product names mentioned may be trademarks or registered trademarks of their respective companies. Specifications are subject to change without notice.